

Callidus CPP+ 380 AM TRX DD EAS system

PRODUCT FEATURES

- Network connection, remote tuning and management
- Buzzer and RGB alarm lights
- MQTT and REST API accessible
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- People counting and alarm validation
- Build-in jamming detection
- Build-in permanent magnet detection
- Build-in booster bag detection
- Optional pager for message transmission
- Transparent or solid version available
- Silver or black colors available
- Different alarm types settings (incoming, outgoing, etc.)
- The system can be set to the 5W energy-saving mode, using a system enable key or programmed schedule, outside store opening hours.
- Easy to use ShopMonitor Lite Dashboard for alarm event management

AVAILABLE ACCESSORIES

- AM deactivator
- ShopMonitor Lite Dashboard
- Bumper

COMPATIBILITY

- AM 58 kHz tags, labels and accessories

MECHANICAL

| | |
|------------|------------------|
| Width | 38.2 cm (15 in) |
| Height | 168 cm (66.1 in) |
| Thickness | 5.5 cm (2.2 in) |
| Base depth | 9.5 cm (3.7 in) |
| Weight | 9.5 kg |

ELECTRICAL

| | |
|---------------------|--|
| Power requirement | 115V/60Hz or 230V/50Hz, 40W max, 5W standby |
| Operating frequency | 58 kHz |
| Alarm mode | Buzzer/RGB alarm indicator |

DETECTION DISTANCE (for DR labels)

| |
|--|
| up to 110 cm (3.61 ft) - each side |
| up to 244 cm (8.01 ft) - TRX-TRX aisle |
| up to 228 cm (7.48 ft) - TRX-RX aisle |

ENVIRONMENTAL

| | |
|---------------------|--|
| Ambient temperature | 0–35°C (equipment for normal indoor use) |
| Relative humidity | 0–90% (non-condensing) |

PRODUCT ORDER CODES

| | |
|-----------------------------------|-------------------|
| CPP+ 380 AM TRX with EU UL PSU | 18-501.TPDDABC-EU |
| with US UL PSU | 18-501.TPDDABC-US |
| with UK UL PSU | 18-501.TPDDABC-UK |
| CPP+ 380 bumper | 19-061.38 |

