

## Callidus S1000 AM deactivator

### PRODUCT FEATURES

- Compact design, internal power supply
- Vertical, horizontal or undercounter installation allowed
- Compatible with wide range of deactivation pads
- One control unit can drive one deactivation pad
- Possibility to use ShopMonitor Lite Dashboard for device monitoring
- Auto synchronization to the nearest AM systems
- Standard mode (detection and deactivation), tag-checker mode only, standby mode, switch ON/OFF deactivation by key
- Network connection, remote tuning and management via eComm device or via HW key (local connection)

### AVAILABLE ACCESSORIES

- ShopMonitor Lite Dashboard
- eComm

### COMPATIBILITY

- AM 58 kHz tags, labels and accessories
- AM S1000 deactivation pads and POS scanner loops

### MECHANICAL

- Length 18.7 cm (7.36 in)
- Width 17 cm (6.69 in)
- Height 5.2 cm (2.05 in)
- Weight 1.7kg

### ELECTRICAL

- Power requirement 115V/60Hz or 230V/50Hz, 20W max, standby mode 4W
- Operating frequency 58 kHz
- Status indication Buzzer, LED indicators

### DETECTION/DEACTIVATION DISTANCE

Up to 25/18 cm, depending on the AM deactivation pad connected

### ENVIRONMENTAL

Ambient temperature  
Relative humidity

0–35°C (equipment for normal indoor use)  
0–90% (non-condensing)

### PRODUCT ORDER CODES

Callidus AM deactivator S1000  
230V/50Hz version  
115V/60Hz version

13-047.C (R2)  
13-047.C115(R2)

