

### Callidus AM floor 166x74 U10 concealed EAS system

#### PRODUCT FEATURES

- AM EAS system designed for floor installation
- Very slim design, no ferrite shielding needed
- Invisible installation under the floor (pic.1). Possibility of multiple installations for large entrances (pic.2)
- Compatible with AM TRX control box and AM TRX ceiling extenders for large detection distance
- System features and detection distances according to connected control unit

#### COMPATIBILITY

- AM TRX

#### MECHANICAL

- Dimensions 170 x 77.5 x 3 mm (67x30.5x1.2 in)
- Weight 7 kg
- Connecting cable length 10 m

#### ELECTRICAL

- Power requirement AM TRX control box needed
- Operating frequency AM 58kHz frequency range

#### DETECTION HEIGHT (for DR labels)

- Full area detection height up to 125cm (no extenders)
- No detection gap up to 280 cm (AM TRX control box, with AM TRX ceiling extenders)
- No detection gap up to 330 cm (AM TRX control box, with AM TRX ceiling floor system)

#### ENVIRONMENTAL

- Ambient temperature 0–35°C (equipment for normal indoor use)
- Relative humidity 0–90% (non-condensing)

#### PRODUCT ORDER CODES

- AM floor 166x74 U15 concealed 17-550.U10
- Callidus AM TRX controller 19-014.Cxx



Pic.1



Pic.2