

Callidus AM TRX controller with UL power supply

PRODUCT FEATURES

- One control unit can drive one pedestal or floor system
- Compatible with wide range of detection antennas
- Network connection, remote tuning and management
- UL power supply included (100 - 240V/50 - 60Hz)
- Build-in jamming detection
- Optional foil bag and/or permanent magnet detection
- Embedded buzzer
- Energy efficient - about 20W power consumption
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- Intelligent electricity saving modes

AVAILABLE ACCESSORIES

- ShopMonitor Lite Dashboard

COMPATIBILITY

- AM 58 kHz tags, labels, deactivators and accessories

MECHANICAL

- Length 31 cm (12.20 in)
- Width 24 cm (9.45 in)
- Height 4.6 cm (1.81 in)
- Weight 2.4 kg

ELECTRICAL

- Power requirement 100-240V/50-60Hz, 35W max, standby mode cca 6 W
- Operating frequency 58 kHz

ENVIRONMENTAL

- Ambient temperature 0 - 35°C (equipment for normal indoor use)
- Relative humidity 0 - 90% (non-condensing)

PRODUCT NAME

Callidus AM TRX controller with UL power supply:

- with EU mains cable
- with US mains cable
- with UK mains cable
- with BRA mains cable
- with AUS mains cable

ShopMonitor Lite Dashboard

ORDER CODES

- 19-014.CEU
- 19-014.CUS
- 19-014.CUK
- 19-014.CBR
- 19-014.CAU

17-018.C-BX

