

Callidus AM TRX 166x74 U4 concealed EAS system

PRODUCT FEATURES

- AM EAS system designed for floor installation
- Very slim design, no ferrite shielding needed
- Invisible installation under the floor (pic.1). Possibility of multiple installations for large entrances (pic.2)
- Compatible with AM UNI control box and extenders for large detection distance
- Compatible with AM TRX control box for simple installation
- System features and detection distances according to connected control unit

COMPATIBILITY

- AM UNI
- AM TRX

MECHANICAL

- Dimensions 170 x 77.5 x 3 cm (67x30.5x1.2 in)
- Weight 3.8 kg
- Connecting cable length 4 m

ELECTRICAL

- Power requirement AM UNI or AM TRX control box needed
- Operating frequency AM 58kHz frequency range

DETECTION HEIGHT (for DR labels)

- Full area detection height up to 120cm (AM TRX control box or AM UNI control box, no extenders)
- No detection gap up to 230 cm (AM UNI control box, with slender extender)
- No detection gap up to 270 cm (AM TRX control box, with AM TRX ceiling extender)
- No detection gap up to 320 cm (AM TRX control box, with AM TRX ceiling floor system)

ENVIRONMENTAL

- Ambient temperature 0–35°C (equipment for normal indoor use)
- Relative humidity 0–90% (non-condensing)

PRODUCT ORDER CODES

- AM TRX 166x74 U4 concealed system 17-530.U4
- Mandatory for AM TRX version: Callidus AM TRX controller 19-011
- Mandatory for AM UNI version: Callidus AM multipedestal controller 16-021.C-BX (R1)
- Callidus AM FLOOR capacitor tuning box 15-221



Pic.1



Pic.2