

Callidus AM TRX controller

PRODUCT FEATURES

- One control unit can drive one pedestal or floor system
- Compatible with wide range of detection antennas
- Network connection, remote tuning and management
- Internal power supply (100-240V/50-60Hz)
- Build-in jamming detection
- Optional foil bag and/or permanent magnet detection
- Embedded buzzer
- Energy efficient - about 20W power consumption
- Advanced SW features (tag-too-close, adaptive sensitivity adjustment, etc.)
- Intelligent electricity saving modes

AVAILABLE ACCESSORIES

- ShopMonitor Lite Dashboard

COMPATIBILITY

- AM 58 kHz tags, labels, deactivators and accessories

MECHANICAL

- Length 29 cm (11.42 in)
- Width 26 cm (10.24 in)
- Height 4.6 cm (1.81 in)
- Weight 2 kg

ELECTRICAL

- Power requirement 100-240V/50-60Hz, 35W max, standby mode cca 6 W
- Operating frequency 58 kHz

ENVIRONMENTAL

Ambient temperature
Relative humidity

0–35°C (equipment for normal indoor use)
0–90% (non-condensing)

PRODUCT NAME

Callidus AM TRX controller
with EU mains cable
with US mains cable
with UK mains cable
with BRA mains cable
with AUS mains cable

ShopMonitor Lite Dashboard
System licences

ORDER CODES

19-011.CEU
19-011.CUS
19-011.CUK
19-011.CBR
19-011.CAU

17-018.C-BX
see AM TRX Licences brochure

