

Callidus AM TRX 130x74 U4 concealed EAS system

PRODUCT FEATURES

- AM EAS system designed for floor installation
- Very slim design, no ferrite shielding needed
- Invisible installation under the floor (pic.1). Possibility of multiple installations for large entrances (pic.2)
- Compatible with AM TRX control box for simple installation
- System features and detection distances according to connected control unit

COMPATIBILITY

- AM TRX

MECHANICAL

- Dimensions 134 x 77.5 x 3 cm (52.8x30.5x1.2 in)
- Weight 3.5 kg
- Connecting cable length 4 m

ELECTRICAL

- Power requirement AM TRX control box needed
- Operating frequency AM 58kHz frequency range

DETECTION HEIGHT (for DR labels)

- Full area detection height up to 120 cm (no extenders)
- No detection gap up to 270 cm (AM TRX control box, with AM TRX ceiling extender)
- No detection gap up to 320 cm (AM TRX control box, with AM TRX ceiling floor system)

ENVIRONMENTAL

- Ambient temperature 0–35°C (equipment for normal indoor use)
- Relative humidity 0–90% (non-condensing)

PRODUCT ORDER CODES

- AM TRX 130x74 U4 concealed 17-535.U4
- Callidus AM TRX controller 19-014.Cxx



Pic.1



Pic.2